SUPER FLUX LED LAMP, 4PIN LED

BL-FL760Rxx

Features:

- 7.62*7.62*3.5MM, flat round top, SUPER FLUX LED LAMP
- Ultra brightness.
- Wide Viewing Angles.
- Ideal For Backlight and Indicator
- RoHs Compliance

RoHs Compliance

ATTENTION
OBSERVE PRECAUTIONS ELECTROSTATIC SENSITIVE DEVICES


■ Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=70mA)

Part Number	Chip			Lens Type	Forward Voltage(VF) Unit:V		Luminous Intensity (Iv) Unit:mcd		Viewing Angle 2θ1/2 (deg)
	Emitted Color	Material	λP (nm)		Typ	Max	Min.	Typ.	
BL-FL760RURC	Ultra Red	AlGaAs,DDH	660	Water Clear	1.95	2.20	600	1000	160
BL-FL760RUEC	Ultra Red	AlGaInP	630		2.10	2.50	800	1500	
BL-FL760RUYC	Ultra Yellow	AlGaInP	590		2.10	2.50	600	1300	
BL-FL760RUGC	Ultra Green	AlGaInP	574		2.20	2.50	200	700	
BL-FL760RPGC	Ultra Pure Green	InGaN	525		3.10	4.50	1000	5000	
BL-FL760RBGC	Ultra Bluish Green	InGaN	505		3.10	4.50	800	4000	
BL-FL760RUBC	Ultra Blue	InGaN	470		3.10	4.20	800	2000	
BL-FL760RUWC	Ultra White	InGaN	/		3.10	4.20	1000	5000	

■ Absolute maximum ratings (Ta=25°C)


Parameter	UR	UE	UY	UG	PG	BG	UB	W	Unit
Forward Current I_F	25	30	30	30	30	30	30	30	mA
Power Dissipation P_d	60	65	65	75	110	110	120	120	mW
Reverse Voltage V_R	5	5	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	100	100	100	mA
Operation Temperature T_{OPR}	-40 to +80								°C
Storage Temperature T_{STG}	-40 to +85								°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)								°C

■ Package configuration & Internal circuit diagram




Notes:
1. All dimensions are in millimeters (inches)
2. Tolerance is ±0.25(0.01")unless otherwise noted.
3. Specifications are subject to change without notice.

■ Typical electrical-optical characteristics curves:




RELATIVE INTENSITY Vs WAVELENGTH(λ p)


(1) - GaAsP/GaAs 655nm/Red
(2) - GaP 570nm/Yellow Green
(3) - GaAsP/GaP 585nm/Yellow
(4) - GaAsp/GaP 635nm/Orange & Hi-Eff Red
(5) - GaP 700nm/Bright Red
(6) - GaAlAs/GaAs 660nm/Super Red
(8) - GaAsP/GaP 610nm/Super Red
(9) - GaAlAs 880nm
(10) - GaAs/GaAs & GaAlAs/GaAs 940nm
(A) - GaN/SiC 430nm/Blue
(B) - InGaN/SiC 470nm/Blue
(C) - InGaN/SiC 505nm/Ultra Green
(D) - InGaAl/SiC 525nm/Ultra Green




FORWARD VOLTAGE (Vf)
FORWARD CURRENT VS.
FORWARD VOLTAGE




FORWARD CURRENT (mA)
RELATIVE LUMINOUS
INTENSITY VS. FORWARD
CURRENT




AMBIENT TEMPERATURE Ta(℃)
FORWARD CURRENT VS. AMBIENT
TEMPERATURE



AMBIENT TEMPERATURE Ta(℃)



tp-PULSE DURATION uS
(1,2,3,4,6,8,B.D.J.K)



tp-PULSE DURATION uS
(5)

NOTE:25℃ free air temperature unless otherwise specified

■ Packing and weighting

